## **GKP3** Gaseous Engine

Configuration	Vertical in-line 3-cylinder	
Induction system	Naturally aspirated	
Combustion system	Spark-ignited	
Cooling system	Water-cooled	
Displacement	3.1 L (190 cubic inches)	
Compression ratio	9:1	
Bore x stroke	4.1 x 4.7 inches (105 x 120 mm)	
Direction of rotation	Counterclockwise	
Approx. wet weight	1,044 lbs. (473.6 kg)	
Length	41.0 inches (104.1 cm)	
Width	28.8 inches (73.2 cm)	
Height	40.8 inches (103.6 cm)	
Fuel type	NG/ wellhead/ LPG/ VPG	

50 Hz (1,500 RPM)						
Appli- cation	Fuel	kWe	kWm	ЬНР		
Prime	NG	23	26	34		
Prime	LPG/VPG	24	27	36		
Standby	NG	26	28	38		
Standby	LPG/VPG	27	30	40		

60 Hz (1,800 RPM)						
Appli- cation	Fuel	kWe	kWm	bHP		
Prime	NG	25	28	38		
Prime	LPG/VPG	27	30	40		
Standby	NG	28	31	42		
Standby	LPG/VPG	30	33	44		



Image shown is for illustration purposes only and may not be an exact representation of the final product.

Weight, physical dimensions, and power ratings are for reference only. Final product data is subject to change.